

Rotary & Vibrator Hoses:

Certification : API Spec. 7K FSL1 - FSL2 - ISO 14693 / API Monogram

Operating temperature : -30 to +82°C or -25 to +100°C as specified by purchaser

Maximum available length : 60 m or 200 ft

Production length tolerance: +/- 64 mm up to 6.4 m hose length or +/- 1%



APPLICATIONS:

- Mud delivery hoses
- Mud jumper hoses
- Motion compensator hoses
- Decoking hoses
- Water injection

I.D.	Working Pressure	Test Pressure	API Grade	Safety factor	O.D. Hose Body	MBR Storage	MBR Operation	Weight of Hose Body
in	psi	psi	-	* WP	mm	m	m	kg/m
2	4000	8000	C	2.5	97	0.6	0.7	11
2	5000	10000	D	2.5	102	0.6	0.7	12
2.5	4000	8000	C	2.5	109	0.6	0.7	13
2.5	5000	10000	D	2.5	111	0.6	0.7	15
2.5	7500	15000	E	2.5	132	0.7	0.8	25
3	4000	8000	C	2.5	124	0.6	0.7	16
3	5000	10000	D	2.5	126	0.7	0.8	18
3	7500	15000	E	2.5	148	1	1.1	34
3.5	4000	8000	C	2.5	140	0.8	0.9	21
3.5	5000	10000	D	2.5	140	0.8	0.9	21
3.5	7500	15000	E	2.5	162	1.2	1.3	38
4	4000	8000	C	2.5	166	1	1.2	33
4	5000	10000	D	2.5	166	1	1.2	33
4	7500	15000	E	2.5	174	1.2	1.4	41
5	5000	10000	D	2.5	197	1.4	1.5	47
5	7500	15000	E	2.5	213	1.4	1.5	67
6	5000	7500	-	2.25	266	1.5	1.7	57
6	7500	11250	-	2.25	234	1.6	1.8	76

Cement Hose:

Operating temperature : -30 to +82°C or -25 to +100°C as specified by purchaser

Maximum available length : 60 m or 200 ft

Production length tolerance: +/- 64 mm up to 6.4 m hose length, or +/- 1%



APPLICATIONS:

- Cementing hose
- Acidizing hose

API Spec. 7K FSLo - ISO 14693 / API Monogram

I.D.	Working Pressure	Test Pressure	Safety factor	O.D. Hose Body	MBR Storage	MBR Operation	Weight of Hose Body
in	psi	psi	* WP	mm	m	m	kg/m
2	5000	10000	2.5	102	0.6	0.7	12.4
2	10000	15000	2.25	123	0.9	1	26.3
2	15000	22500	2.25	141	1.1	1.4	39.6
2.5	5000	10000	2.5	111	0.6	0.7	15
2.5	10000	15000	2.25	136	1	1.1	30
2.5	15000	22500	2.25	154	1.2	1.5	48
3	5000	10000	2.5	126	0.7	0.8	18
3	10000	15000	2.25	148	1.1	1.2	34
3	15000	22500	2.25	166	1.4	1.6	72
4	5000	10000	2.5	166	1	1.2	33
4	10000	15000	2.25	192	1.5	1.7	61

